

# PRO-SIGNAL



**PSG3030**

**HDMI TO AV CONVERTER**

## IMPORTANT SAFETY INFORMATION

Please read these instructions carefully before use and retain for future reference.

## OVERVIEW

- This device can convert an HDMI digital HD signal into a composite video (CVBS) signal plus the L/R stereo audio signal. It allows digital devices to output to an ordinary TV or monitor which only receives analogue and other CVBS signals. (The composite video standard resolution is 480i & 576i and NTSC and PAL formats).

## WHAT'S IN THE BOX

- Main unit.
- USB power lead
- User's Manual.

## INSTALLATION

- Please make sure all devices you wish to connect have been powered off.
- Connect the source device to the converter using appropriate HDMI cable of up to 10m length (26AWG).
- Connect the output CVBS video to the receiving display.
- Select either NTSC or PAL using the button on the input side.
- Connect the USB DC 5V power cable to the converter and to a device with a suitably equipped USB power socket.
- The power LED lights when the power is applied.

## SPECIFICATIONS

Operating environment	0-40° Humidity <90% / Storage -20 to 60° Humidity <95%
Power supply	220-240V~50Hz
Power requirement	5V DC 600mA
Power consumption (max)	3W
HDMI Input	1080p/1080i/720p/576p/576i/480p
CVBS output resolution	480i/576i
CVBS signal output	0.5~1.0Volts p-p 75ohm
Analogue audio output	0.5~2Volts p-p 47kohm
Dimensions	68 x 51.5 x 16.5mm
Weight (not inc PSU)	65g



### INFORMATION ON WASTE DISPOSAL FOR CONSUMERS OF ELECTRICAL & ELECTRONIC EQUIPMENT.

When this product has reached the end of its life it must be treated as Waste Electrical & Electronic Equipment (WEEE). Any WEEE marked products must not be mixed with general household waste, but kept separate for the treatment, recovery and recycling of the materials used. Contact your local authority for details of recycling schemes in your area.

